# PP DRAINAGE & SEWER SYSTEMS

# **SEWERMAX®**



# GR10300C DN300 x 3m SN10 SewerMAX® Pipe RRJ

**APPLICATION** Used to convey sewage in gravity sewer mains.

### ADDITIONAL INFORMATION Requires DN300 Rubber Ring

Iplex Code: GERSEW300

### **FEATURES**

- Australian Made
- Installation Economics
- Operation Efficiencies
- Abrasion and Chemical Resistant
- · Tree root intrusion resistance
- Smooth bore for hydraulic performance
- Low embodied energy for environmental benefits

# Insertion Depth 147

# **TECHNICAL DATA**

### PRODUCT PROPERTIES

Primary Material	PP
Colour	Grey with yellow internal liner
Joint Type	RRJ
Rubber Ring Material	SBR
Allowable Operation Temperature - Degrees	50°C
Average # of Joints per Litre – Iplex Lubricant	28
Unprotected UV Exposure (years)	2 Years
Maximum Diametric Deflection - 50 Years	7.50%
Minimum Radius of Curvature	75m
Socket Deflection	1°

### **PRODUCT DIMENSIONS**

Category	Length	
Rating	SN10	
Length	3m	
Nominal	343.6mm	
ID	299.5mm	
Wall Thickness	2mm	
Socket Depth	147mm	

Max Socket Nominal OD	414mm
Chamfer Detail	33.2mm
Witness Mark	147mm
Weight	21.7kg
Crate Qty	6
Crate Weight	130.2kg

### **ENVIRONMENTAL CREDENTIALS AND STANDARDS**

Environmental	Accreditation

Environmental Product Declaration (EPD) S-P-00714

**Product Standard** 

AS/NZS 5065 "Polyethylene and polypropylene pipes & fittings for drainage and sewerage applications" AS/NZS 2566.1 'Buried flexible pipelines - Part 1, Structural design & AS/NZS 2566.2 "Buried flexible pipelines - Part 2, Installation"

Standards Mark Certification

Standards Mark Certification SMKP20603

# **MATERIAL PROPERTIES**

### **MECHANICAL**

Density Specific Gravity	0.9
Yield Strain	8%
Compressive Strength	48MPa
Tensile Modulus	31MPa
Creep Ratio	3.3
Hardness Shore D	60
Poissons Ratio	0.45
Ring Bending Strain	4
Ring Bending Modulus (3mins)	1300MPa
Ring Bending Modulus (50Yrs)	200MPa

### **THERMAL**

Coefficient of Thermal Expansion	15x10 <sup>-5</sup> /°C
Thermal Conductivity	0.22W/m.K
Specific Heat	1680 J/kg/°C
Vicat Softening Temperature	95°C
Flammability	Flammable

© Copyright: Iplex Pty Ltd 2019 all rights reserved. All drawings and information contained thereon are the exclusive property of Iplex Pipelines. Unless specifically noted, this drawing and information enclosed are subject to change at any time. Measures are for reference purpose only. If critical please contact Iplex Pipelines.



