PVC NON PRESSURE SYSTEM

STORMWATER



WPSO225 • DN225 x 6m SN2 Stormwater PVC-U Pipe SWJ

APPLICATION Used for above or below ground applications to convey rainwater or surface water

FEATURES

- Australian Made
- BEP PVC Manufactured from Best Environmental Practice PVC
- Installation Economics


- Operation Efficiencies
- Corrosion Resistant
- Tree root intrusion resistance

TECHNICAL DATA PRODUCT PROPERTIES

Primary Material	PVC
Colour	White
Joint Type	SWJ
Allowable Operation Temperature - Degrees	50
Average # of Joints per Litre – Iplex Solvent	6
Average Number of Joints per Litre - Iplex Primer	18
Unprotected UV Exposure (years)	2 Years
Maximum Diametric Deflection - 50 Years	7.50%

PRODUCT DIMENSIONS

Rating	SN2
Length	6m
UOM	LE
Nominal	250mm
ID	239mm
Wall Thickness	5.5mm
Weight	33.5kg
Crate Qty	12
Carton Weight (kg)	402kg



ENVIRONMENTAL CREDENTIALS AND STANDARDS

Carries and sector Assess ditation	Deat Foliage and DMC DMC Coutificate No. DED DMC 0077
Environmental Accreditation	Best Environmental PVC - PVC Certificate No. BEP-PVC 0037

Product Standard

AS/NZS 1254 "PVC-U Pipes and Fittings for Stormwater and Surface Water Applications"

MATERIAL PROPERTIES

MECHANICAL

Density Specific Gravity	1.47
Ultimate Tensile Strength	52MPa
Yield Strain	5.5%
Compressive Strength	66MPa
Tensile Modulus	2750MPa
Hardness Shore D	85
Poissons Ratio	0.38
Ring Bending Modulus (3mins)	3200MPa
Ring Bending Modulus (50Yrs)	1400MPa

THERMAL

Coefficient of Thermal Expansion	7x10 ⁻⁵ /°C
Thermal Conductivity	0.138W/m.K
Specific Heat	1047 J/kg/°C
Vicat Softening Temperature	75°C
Flammability	Will not support combustion
Fire Index – Ignitability	8
Fire Index – Smoke Development	8
Fire Index – Spread of Flame	0
Fire Index – Heat Evolved	1

© Copyright: Iplex Pty Ltd 2019 all rights reserved. All drawings and information contained thereon are the exclusive property of Iplex Pipelines. Unless specifically noted, this drawing and information enclosed are subject to change at any time. Measures are for reference purpose only. If critical please contact Iplex Pipelines.



